


# STACKING S 30 V NAKED - INDOOR


David Rockwell, 2023



Discover more

REPLACEABLE LED

## TECHNICAL SHEET

MATERIALS	Difuser: Polymethacrylate Structure: Aluminum
DIMENSIONS	Difuser: [Ø2 7/8" H11 3/4"] Ø7,5cm H30cm Canopy: [Ø7 1/8" H1 7/8"] Ø18cm H4,9cm Cable length: [118 1/8"] 300cm
CANOPY	Matte White
LIGHT SOURCE	5 X LED STRIP 6,25W (total) 547 lm (delivered) 3000K CRI≥90 5 X LED STRIP 6,25W (total) 536 lm (delivered) 2700K CRI≥90
DIMMING PROTOCOL	0/1-10V; Phase cut
MARKING	DRY LOCATION 
NET WEIGHT	3,74 Ibs

PROJECT NAME	
SPECIFIER NAME	

We reserve the right to change our product specifications.  
Please visit [www.leucos.com](http://www.leucos.com) for the latest product information

North America

LEUCOS



### 100-277Vac 50-60Hz standard version

(supplied with canopy & driver)

DIMMING PROTOCOL	0/1-10V; Phase cut			
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE	QTY	TYPE
Transparent + Anodized Aluminum	LED 3000K	0012509		
	LED 2700K	0012510		

### 24Vdc version installation with remote driver

(supplied without canopy & driver)

DIMMING PROTOCOL	Driver and canopy not included			
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE	QTY	TYPE
Transparent + Anodized Aluminum	LED 3000K	0013391		
	LED 2700K	0013392		