


STACKING S 180 H RIG - INDOOR


David Rockwell, 2024



Discover more


REPLACEABLE LED

TECHNICAL SHEET

MATERIALS	Diffuser: Blown Borosilicate Glass Structure: Aluminum
DIMENSIONS	Diffuser: [04" L70 7/8"] Ø10cm L180cm Canopy: [15 3/4" x 2 3/4" x H1 5/8"] 40cm x 7cm x H4cm Cable length: [118 1/8"] 300cm
CANOPY	Matte White
LIGHT SOURCE	5 X LED STRIP 43,75W (total) 3830 lm (delivered) 3000K CRI≥90 5 X LED STRIP 43,75W (total) 3539 lm (delivered) 2700K CRI≥90
DIMMING PROTOCOL	0/1-10V; Phase cut
MARKING	DRY LOCATION 
NET WEIGHT	27,11 Ibs

PROJECT NAME	
SPECIFIER NAME	

We reserve the right to change our product specifications.
Please visit www.leucos.com for the latest product information



100-277Vac 50-60Hz standard version (supplied with canopy & driver)

DIMMING PROTOCOL	0/1-10V; Phase cut			
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE	QTY	TYPE
Transparent Rigadin + Anodized Aluminum	LED 3000K	0013571		
	LED 2700K	0013572		
Transparent Rigadin + Matte Black Aluminum	LED 3000K	0013914		
	LED 2700K	0013915		
Tobacco Rigadin + Anodized Aluminum	LED 3000K	0013772		
	LED 2700K	0013773		
Tobacco Rigadin + Matte Black Aluminum	LED 3000K	0013776		
	LED 2700K	0013777		

24Vdc version installation with remote driver (supplied without canopy & driver)

DIMMING PROTOCOL	Driver and canopy not included			
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE	QTY	TYPE
Transparent Rigadin + Anodized Aluminum	LED 3000K	0013573		
	LED 2700K	0013574		
Transparent Rigadin + Matte Black Aluminum	LED 3000K	0013780		
	LED 2700K	0013781		
Tobacco Rigadin + Anodized Aluminum	LED 3000K	0013774		
	LED 2700K	0013775		
Tobacco Rigadin + Matte Black Aluminum	LED 3000K	0013778		
	LED 2700K	0013779		