


# STACKING S 30 V RIG - INDOOR

David Rockwell, 2024

North America

**LEUCOS**



Discover more

REPLACEABLE LED



## 100-277Vac 50-60Hz standard version


(supplied with canopy & driver)

DIMMING PROTOCOL	0/1-10V; Phase cut			
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE	QTY	TYPE
Transparent Rigadin + Anodized Aluminum	LED 3000K	0013587		
	LED 2700K	0013588		
Transparent Rigadin + Matte Black Aluminum	LED 3000K	0013922		
	LED 2700K	0013923		
Tobacco Rigadin + Anodized Aluminum	LED 3000K	0013812		
	LED 2700K	0013813		
Tobacco Rigadin + Matte Black Aluminum	LED 3000K	0013816		
	LED 2700K	0013817		

## 24Vdc version installation with remote driver

(supplied without canopy & driver)

DIMMING PROTOCOL	Driver and canopy not included			
FINISH (DIFFUSER + STRUCTURE)	SOURCE	CODE	QTY	TYPE
Transparent Rigadin + Anodized Aluminum	LED 3000K	0013589		
	LED 2700K	0013590		
Transparent Rigadin + Matte Black Aluminum	LED 3000K	0013820		
	LED 2700K	0013821		
Tobacco Rigadin + Anodized Aluminum	LED 3000K	0013814		
	LED 2700K	0013815		
Tobacco Rigadin + Matte Black Aluminum	LED 3000K	0013818		
	LED 2700K	0013819		

TECHNICAL SHEET	
MATERIALS	Diffuser: Blown Borosilicate Glass Structure: Aluminum
DIMENSIONS	Diffuser: [04" H11 3/4"] Ø10cm H30cm Canopy: [07 1/8" H1 7/8"] Ø18cm H4,9cm Cable length: [118 1/8"] 300cm
CANOPY	Matte White
LIGHT SOURCE	5 X LED STRIP 6,25W (total) 541 lm (delivered) 3000K CRI≥90 5 X LED STRIP 6,25W (total) 530 lm (delivered) 2700K CRI≥90
DIMMING PROTOCOL	0/1-10V; Phase cut
MARKING	DRY LOCATION 
NET WEIGHT	5,60 Ibs

PROJECT NAME	
SPECIFIER NAME	

We reserve the right to change our product specifications.  
Please visit [www.leucos.com](http://www.leucos.com) for the latest product information